

TR-200 Pickup Refrigeration Units

A cooling system designed for the transportation of fresh or frozen goods in small truck with container volume of 6~15m³.

- Multi-function controller with microprocessor control system
- Extra-flat evaporator with inner grooved cooper tube; micro-channel parallel flow condenser
- Digital display: temperature in °C or °F; return air; configuration parameters and alarms
- Safety devices: low and high refrigerant pressure protection; thermal protection

Model		TR-200
Temperature Range In Container		-30°C ~ +30°C
		0°F ~ +86°F
Cooling Capacity	0°C/+32°F	2200W / 2559Kcal/h / 7550 BTU
	-18°C/ 0°F	1127W / 1311Kcal/h / 3840 BTU
Compressor	Model	SD-5S11
	Displacement	108cc/r
	Weight	5.4KG
Condenser	Coil	Aluminum micro-channel parallel flow coils
	Fan	One fan(DC12V/24V)
	Dimensions	760×553×230 mm
	Weight	16 kg
Evaporator	Coil	Copper Tube & Aluminum Fin
	Fan	One Italy Spal Fans (DC12V/24V)
	Dimensions	603×538×230 mm
	Weight	13 kg
Voltage		DC12V / DC24V
Refrigerant		R404a/1.2kg
Defrosting		Hot gas defrosting(Auto./Manual)
Application		6~15m ³

Application

