

TR-300T Direct Driven Units

Driven Type:	Vehicle Engine Driven Units
Installation:	Split Front Mounted
Compressor	QP15 138cc/r
Controller	Digital, In Cab
Application:	10~16m ³

Features

- ◆ Roof mounted unit and slim evaporator design
- ◆ Strong refrigerating and cooling fast
- ◆ High-strength plastic enclosure and elegant appearance
- ◆ Compact structure, small size, light weight and fuel savings
- ◆ Quick installation, simple maintenance and low maintenance cost
- ◆ Apply to all kinds of small refrigerated vans

Specification

Model		TR-300T
Temperature Range In Container		-18℃ ~ +30℃ / -0.4°F ~ +86°F
Cooling Capacity		3000W/2580Kcal/10236BTU (0℃/32°F) 1600W/1376Kcal/5460BTU (-18℃/-0.4°F)
Driven Model		Direct Vehicle Engine Driven
Voltage DC (V)		12V/24V
Refrigerant		R404a
Refrigerant Charge		1.7Kg ~ 1.8Kg
Box Temperature Adjustment		Electronic digital display
Safety Protect		High and low pressure switch
Defrosting		Hot gas defrost (CPR)
Compressor	Model	SD5S14(138CC/r) /QP15
Condenser	Coil	Aluminum micro-channel parallel flow coils
	Fan	2 Axial Fan
	Dimensions&Weight	800×865×210 mm & 31.8 kg
Evaporator	Coil	Aluminum foil with internal ridge copper tube
	Fan	2 Axial Fans
	Dimensions&Weight	850×550×175 mm & 14.4 kg
Box Volume (m ³)		10m ³ (-18℃/-0.4°F) 16m ³ (0℃/32°F)
Optional Function		Heating, Electric standby system AC 220V/380V, CPR Valve

Zhengzhou Guchen Thermo Co.,Ltd.
www.guchenthermo.com
info@guchenthermo.com
Tel: +86-371-69152892
Fax: +86-371-69152894



Product PHOTOS

